

THOMSON

THOMSON TG787 Wireless VoIP Residential Gateway



Data Voice Video

TELECOM

SATELLITE

CABLE

TERRESTRIAL

| Best in Class in Digital and Voice Communication

The THOMSON TG787 is a Voice over IP Gateway allowing ADSL connectivity while providing Voice over IP functions for residential and business users. The THOMSON TG787 offers next to 4 Ethernet ports, an additional 802.11b/g wireless LAN interface, and supports ADSL2+. It is also backwards compatible with ADSL offering autonegotiation capability.

| Home Networking with Easy Installation

Like all THOMSON gateways, the THOMSON TG787 is provided with the Home Install Wizard, making the setup of a wireless home network as easy as clicking a button. No more helpdesk calls, just click and you are ready to go. The Home Install Wizard performs comprehensive system checks before and during the installation and setup process, and validates all user inputs to guarantee the end user a secured wireless connection to the Internet.

| Easily Manageable

The THOMSON TG787 is completely designed according to the TR-069 Data Model, through which the device can be configured remotely. In addition, TR-104 for VoIP is implemented for the configuration and management of all voice services.

TR-037 enables auto-configuration of network bandwidth according to service needs, allowing seamless integration with the network's provisioning system.

| Voice over IP

The THOMSON TG787 offers two phone connectors to accommodate a phone and fax. Once the gateway is registered with a VoIP service, regular phone calls can be conducted over the Internet with all the benefits of IP Telephony. The gateway offers a wide range of services like caller ID, CLIR, call waiting, call forwarding, 3-way conference and message waiting notification.

THOMSON
images & beyond

THOMSON TG787

Wireless VoIP Residential Gateway

TELECOM

SATELLITE

CABLE

TERRESTRIAL



| Advanced in Security

The integrated firewall guarantees users ultimate network security. The firewall minimizes undesired service impact and provides stateful inspection of packets. An integrated Denial of Service (DoS) engine monitors a wide range of attack patterns, and logs potential security breaches to a local cache or remote server.

The THOMSON TG787 also supports powerful wireless security mechanisms, such as Wi-Fi Protected Access (WPA™), Wired Equivalent Privacy (WEP™) encryption, and a physical registration button. This allows users to communicate and access data with efficient link quality and the highest level of network security. Unwanted content filtering on the Internet is also integrated.

| Features in a glance

- Wireless networking on-board: 11b/g and 11.n ready
- ADSL with integrated modem
- 1 FXO analogue port
- 2 FXS ports for phone and/or fax
- 4 Ethernet ports to connect multiple devices, such as PCs, laptops, set top boxes...
- 1 USB 2.0 master for hard disk, printer, DECT dongle...
- Optional 2nd USB master
- Home entertainment ready
- Media sharing - UPnP A/V
- Remotely manageable - TR-069, TR-104, TR-098, TR-111
- Built-in firewall
- Optional integrated filter

Technical Specifications

Hardware Specifications

Interfaces

WAN

- RJ11 DSL line port
- Optional ISDN (Annex B)
- Full FXO

LAN

- 4-port autosensing 10/100Base-T auto-MDI/MDI-X Ethernet switch
- 2 FXS POTS interfaces
- 1 USB 2.0 master
- Wi-Fi IEEE 802.11b/g on board
- Mini PCI 11n TELCO (802.11b/g/n)

Possible HW extension

- Second USB 2.0 master

Extras

External dipole antenna

Restore factory defaults button

WLAN/DECT registration button

Dimensions (h x d x w)

37 x 181 x 257 mm (1.5 x 7.1 x 10.2 in.)

AC Voltage

220-240 VAC / 100-120 VAC

Temperature

0° - 40° C (32 - 104 F)

Humidity

20% to 80%

DSL Modem Specifications

- Supports Multi Mode Standard
- ADSL ANSI T1.413 Issue 2, ITU G.992.1 Annex A (G.dmt), ITU G.992.2 Annex A (G.lite), ITU G.994.1 (G.hs)
 - Maximum Rate: 8 Mbps for downstream and 1 Mbps for upstream
- ADSL2 ITU G.992.3 Annex A (G.dmt.bis), ITU G.992.4 Annex A (G.lite.bis)
 - Maximum Rate: 12 Mbps for downstream and 1.5 Mbps for upstream
- ADSL2+ ITU G.992.5 Annex A
 - Maximum Rate: 24 Mbps for downstream and 1.3 Mbps upstream

Firewall Security

- Firewall with Stateful Packet Inspection
- Protection of Denial of Service (DoS) such as SYN Flood, Ping of Death, Fraggle, LAND, Teardrop, etc.
- Content filtering: URL blocking
- IP and generic packet filtering, based on IP address/port number/protocol type
- Real-time attack alert and logging

Management

- User Friendly GUI via HTTP and HTTPS
- (Wireless) Home Network Install Wizard
- Web based Easy installation (OS independent)
- On demand Remote Management
- TR-69 Remote Manageable
- TR-104 Voice Provisioning
- TR-98 Queue Management
- TR-111 Home Network Device Management

Services

- Printer sharing
- Content sharing (UPnP A/V + SMB)
- Webcam control and display
- Secure Remote File Access
- PC-less Peer-2-Peer
- Personal Web Gallery
- Shared HD with Access Rights
- Gateway Secured Storage
- Central PVR

Wireless Performance and Security

- Wi-Fi® CERTIFIED™ 802.11b/g access point
 - data rates up to 54Mb/s
- Wi-Fi Multimedia - WMM™ (802.11i)
- Supports 802.1x/ PSK WPA™
- WPA™-Personal / WPA2™-Personal (802.11i)
- Supports wireless repeater function to extend the coverage area
- Dynamic rate switching for optimal wireless data rates up to 54 Mb/s
- Manual/auto radio channel selection
- Manual/auto selection of pure 802.11g/mixed mode (802.11b/g) network
- Wireless Distribution System (WDS)
- 64/128bit WEP encryption
- Wireless client MAC or hardware address-based access control (with physical registration button)

Enabling Technologies

- Qos: ATM, Ethernet, Wi-Fi, IP
- FLEXIBundLE
- Hyper-Nat
- «SIM-lock»
- Virtual bridges - portmapping
- Flexiport
- Smart DHCP, DNS
- IGMPv3 proxy (Fastleave)
- IGMP snooping
- VLAN bridging - tagging

Technical Specifications

Voice over IP Features

Voice Functionality

- Signalling: SIP, MGCP, H.323(0)
- Codecs: G.711, G.723, G.726, G.729, Wideband (G.722), T.38
- Flexible Telephone number per FXS and DECT Handsets, including Common Numbers
- Interop with main market softswitches

FXO

- Dial map for PSTN/VoIP outgoing calls
- Prefix for PSTN/VoIP switch
- Lifeline backup: manual and automatic PSTN / VoIP
- Incoming call detection on PSTN

Supplementary and Advanced Services

- Call waiting (on call basis)
- Caller Identification
- Call forwarding (No answer/Busy/Unconditional)
- Call transferring
- CLIP (Calling Line Identification Presentation)
- CLIR (Calling Line Identification Restriction)
- Fax transparency
- 3-way conference
- MWI (Message Waiting Indicator)
- Missed call e-mail
- Click to dial
- Warm line
- Call Completion to Busy Subscriber
- Forced FXO
- Abbreviated number
- Common DECT number
- Common number in/outgoing Call

Content of the Box

- Wireless VoIP Residential Gateway
- ADSL cable (RJ11)
- Ethernet cable
- Power supply unit
- CD-ROM including QIG, user manual and Home Install Wizard
- Safety Instructions Leaflet
- Filter or splitter (optional)
- Foot and inlay (optional)

* Windows® is a registered trademark of Microsoft Corporation in the United States and other countries

** Wi-Fi CERTIFIED™ is a registered certification mark and WPA™, WPA2™, WPA™-Personal, WPA2™-Personal, and WMM™ are trademarks of the Wi-Fi Alliance

** UPh™ is a certification mark of the UPh™ Implementers Corporation



For more information

THOMSON | 46, quai Alphonse Le Gallo | 92100 Boulogne-Billancourt | France
Tel. : 33 (0) 1 41 86 50 00 | Fax : 33 (0) 1 41 86 56 59 | www.THOMSON-broadband.com

© 2007 THOMSON Inc.- Trademark(s) ® Registered\ -Marca(s)
Registrada(s)\
Photos and features subject to change without notice.