



802.11a/b/g Outdoor Client Bridge / Access Point

EOC-8610 EXT

The EOC-8610 EXT utilizes an Atheros AR5006 solution and up to 400 mW RF output power in a IP67 rated enclosure to provide extended wireless signal coverage outdoors. Along with integrated 802.3af support, versatile operation modes, and security support for WEP, WPA, WPA2, make the EOC-8610 EXT the ideal outdoor wireless solution.

Specifications

General:

- High Speed Data Rates up to 54Mbps for heavy data payloads like video streaming.
- Fully interoperable with IEEE802.11a/b/g compliant devices
- Weatherproof IP67 enclosure with lightning suppression.
- WPA and 802.1x support for data protection.
- WDS (Wireless Distribution System) in Access Point mode.
- SNMP support for easy remote management.
- 802.3af Power-over-Ethernet certified.

Radio:

- **Frequency Band:**
802.11a: 5.15-5.25GHz, 5.25-5.35GHz, 5.47-5.725GHz, 5.725-5.825GHz
802.11b/g: 2.4-2.484 GHz (USA)
- **Media Access Protocol:**
Carrier Sense Multiple Access with Collision Avoidance (CSMA/CA)
- **Modulation Technology:**
Orthogonal Frequency Division Multiplexing (OFDM)
DBPSK @ 1Mbps
DQPSK @2Mbps
CCK @ 5.5 & 11Mbps
BPSK @ 6 and 9 Mbps
QPSK @ 12 and 18 Mbps
16-QAM @ 24 and 36 Mbps
64-QAM @ 48 and 54 Mbps
- **Operating Channels**
802.11b/g: 11 (North America)
802.11a: 12 non-overlapping channels (North America)
- **Receive Sensitivity (Typical)**
5.15 - 5.85G(IEEE802.11a)
6Mbps@ -88dBm
54Mbps@ -70dBm
2.412 - 2.472G(IEEE802.11g)
6Mbps@ -91dBm
54Mbps@ -74dBm
2.412 - 2.472G(IEEE802.11b)
11Mbps@ -90dBm
1Mbps@ -95dBm
- **Available Transmit Power (Typical)**
5.15 - 5.24 GHz(IEEE802.11a)
17dBm @6 - 24Mbps
17dBm @36Mbps
16 dBm @48Mbps
15 dBm @54Mbps
5.26 - 5.35GHz(IEEE802.11a)
20dBm @6 - 24Mbps
18dBm @36Mbps
16 dBm @48Mbps
15 dBm @54Mbps
5.745 - 5.85GHz (IEEE802.11a)
18dBm @6 - 24Mbps
16dBm @36Mbps
14 dBm @48Mbps
13 dBm @54Mbps

- 2.412-2.472G(IEEE802.11g)
26dBm @6 - 24Mbps
23dBm @36Mbps
22 dBm @48Mbps
21 dBm @54Mbps
- 2.412-2.472G(IEEE802.11b)
Up to 26 dBm. @1, 2, 5.5 and 11Mbps

• RF Connector:

RP-SMA Type

Networking:

- **Topology**
Ad-Hoc, Infrastructure
- **Operation Mode**
Point-to-Point/ Point-to-Multipoint Bridge/ AP/ Client Bridge/ WDS
- **Interface**
Wireless IEEE802.11b/g
10/100 RJ-45 port
- **Security**
AP Mode: IEEE802.1x / RADIUS Client (EAP-MD5/TLS/TTLS)
WPA /WPA2/ Pre Share KEY (PSK) with TKIP/AES
MAC address filtering (AP only)
Hide SSID
- **IP Auto-configuration**
DHCP client/server

Management:

- **Configuration**
Web-based configuration (HTTP)
Telnet Configuration
SNMP

Firmware Upgrade:

- Upgrade firmware via web-browser
Serial Interface (RS-232)

Physical:

- **Dimensions (H x W x D)**
163.8(L)mm x 135.2(W)mm x 47.0(H)mm
- **Weight**
1.2 Kg (2.6 lbs)
- **Environment Temperature Range**
Operating: -20°C to 60°
Storage: -40°C to 80°
- **Humidity (non-condensing)**
5%-95% Typical
- **Package Contents**
1 Outdoor Wireless Client Bridge/Access Point Unit
1 48V, 0.375A AC/DC adapter with wall-plug power code
1 One Dual Band SMA Antenna.
1 Inline Power Injector (PoE)
1 1.8m Grounding Cable
1 User manual CD-disc
1 Wall mounting kit
1 Mast mounting kit



1580 Scenic Avenue
Costa Mesa, CA 92626
Toll Free: 888.735.7888

Tel: 714.432.8668
Fax: 714.432.8667
www.engeniustech.com

© 2006, EnGenius Technologies Inc, Proprietary & Confidential

*All specifications are subject to change by EnGenius without prior notice.