



global solutions :
local support™

4900-5850 MHz Omnidirectional Antenna Vertical Polarization

The OD5WM wide band omnidirectional antenna by Laird Technologies is one of a series of omnidirectional antennas that have been optimized for direct chassis mount to outdoor radios or NEMA enclosures. These antennas come standard with an integrated N male connector directly mounted to the base of the antenna. The rugged directly mounted connector is perfect for outdoor mesh applications that often require the antenna to be directly mounted to the radio or enclosure. The antenna is enclosed in a UV stable, water resistant housing to provide years of trouble free service. A mast mount hardware kit is available for applications that require the antenna to be remotely mounted from the radio enclosure.

Features and Benefits:

- 8dBi Gain
- Wide band operation
- Type N male integrated connector
- Extremely rugged for long service life in extreme environments

Applications

- 4.9 to 5.8 GHz mesh applications
- 802.11a wireless systems
- Hot spots
- Point to multi-point systems
- Metropolitan networks
- WiFi access points
- 4.9GHz public safety

For sales information:

Telephone 801-572-3024


E-Mail sales@pacwireless.com

or visit: www.pacwireless.com


SPECIFICATIONS

Frequency:	4900-5850 MHz
Gain:	8 dBi
Elevation beamwidth:	16°
Azimuth beamwidth:	360°
VSWR:	< 2.0:1
Polarization:	Vertical Linear
Weight:	0.37 Lbs (0.17 kg)
Dimensions:	11.5"x1" (292 x 25 mm)
Wind survival rating:	125 mph
Power:	5 watts max
RF Connectors:	N Male

ANTENNA PATTERNS



E Plane



H Plane

SYSTEM ORDERING:

OD5WM-8 4900-5850 MHz Wide Band Omnidirectional Antenna 8dBi

SUGGESTED ACCESSORY



N Female extended Bulkhead to
SMA Female adapter for mounting a
Mesh Omni in an enclosure
Part # AD-NFB-SMAF

NOTES:

- All shipments F.O.B. Bluffdale, UT 84065
- All antennas carry a 2 Year Warranty

Any information furnished by Laird Technologies and its agents is believed to be accurate and reliable. Responsibility for the use and application of Laird Technologies materials rests with the end user since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability, or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies domestic terms and conditions of sale in effect from time to time, a copy of which will be furnished upon request.

Specifications subject to change without notice.

